



Dual Speed Switch Fitted

4" (100mm) CFM High 116 cfm - Low 97 cfm

5" (125mm) CFM High 167 cfm – Low 145cfm

6" (150mm) CFM High 311 cfm - Low 241 cfm

8" (200mm) CFM High 493 cfm - Low 405 cfm

GroFAN PARAMETER (4" 5" 6" 8")

| code | Stalls | Current | Power | Speed | Weight | Air Flow | Air Pressure | dBA 3m | Tent Size |
|---------------|--------|---------|-------|-------|--------|----------|--------------|--------|-----------|
| | | (Amps) | (W) | (RPM) | (Kg) | (M3/H) | (Pa) | (db) | (M3) |
| GF100 (4") | H | 0.12 | 26 | 2200 | 2.0 | 198 | 156 | 31 | < 2 |
| | L | 0.11 | 23 | 1850 | | 165 | 131 | 26 | m3 |
| GF125 (5") | H | 0.14 | 33 | 2250 | 2.2 | 284 | 159 | 31 | < 3 |
| | L | 0.13 | 28 | 1850 | | 248 | 106 | 26 | m3 |
| GF150 (6") | H | 0.24 | 54 | 2550 | 2.7 | 530 | 300 | 33 | < 6 |
| | L | 0.21 | 48 | 1850 | | 410 | 240 | 29 | m3 |
| GF200 (8") | H | 0.57 | 128 | 2450 | 4.9 | 840 | 352 | 63 | < 10 |
| | L | 0.52 | 123 | 1950 | | 690 | 274 | 55 | m3 |